



Dimensions

| | |
|-------------------------|-----------|
| Product dimensions (mm) | ø100 x 87 |
| Net weight (g) | 100 |
| Gross weight (Kg) | 0,12 |

Product

| | |
|-----------------------------|--------------------|
| IP | 68 |
| IK | 4 |
| Electrical class insulation | Class 1 |
| Operating temperature | from -20°C to 35°C |
| Electrical feeding | 220..240V, 50/60Hz |
| Colour | Anthracite |

Control gear

| | |
|--------------|--------------|
| Control gear | Without Gear |
|--------------|--------------|

Light source

| | |
|-----------------------|--------------------------------|
| Light source | Halogen or retrofit equivalent |
| Lamp holder | GU10 |
| Nominal power (W) | 35 |
| Average life time (h) | 2000 |
| Voltage (V) | 220-240V; 50/60 Hz. |
| Diameter (mm) | 51 |
| Lamp | QPARCB |

Small format outdoor projector from the TROLL family Single.

DESCRIPTION

Small format outdoor projector from the TROLL family Single setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of optimised to be used as accent lighting in garden projects. Designed for floor wall or ceiling surface mounted. Spike for land installation included. Body built in extruded aluminium with frontal protection made of tempered glass finished in anthracite. Luminaire is IP68. and sets a max. 35 W QPAR-16 (not supplied) fed at 220-240V; 50/60 Hz.

| | |
|---------------------------|--|
| Item code | 11.0779.0001.22 |
| Product type | OUT |
| Category | Projectors |
| Family | Single |
| Subfamily | Single |
| Materials | Body built in extruded aluminium with frontal protection made of tempered glass. |
| Optical system | Luminaire built-in a. |
| Installation instructions | Luminaire designed for floor wall or ceiling surface mounted. |

Pictograms

