




Dimensions

Product dimensions (mm) Ø264 x 105

Scheme

Scheme



Product

Real power (W) 10

Real luminous flux (Lm) 201

Luminous efficiency (Lm/W) 20,1

Beam angle (°) 105

Life time (h) 50000

IP 54

Electrical class insulation Class 1

Operating temperature from -20°C to 35°C

Electrical feeding 220..230V, 50/60Hz

Colour Anthracite

Energy efficiency class A

Control gear

Control gear included Yes

Control gear Electronic Control Gear

Factor de potencia 0,9

Light source

Light source included Yes

Light source Led

Nominal power (W) 9


Nominal luminous flux (Lm) 450

Colour temperature (K) 3000

CRI 80

Photometry

Photometry



Outdoor sconce from the TROLL family Apliques.

DESCRIPTION

Outdoor sconce from the TROLL family Apliques setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 3000° K (warm white) optimised to be used as general lighting of passing areas, entrances, staircases or similar areas. Designed for wall surface mounted. Luminaire body built in die-cast aluminium finished in anthracite. Luminaire is IP54. Luminaire built-in an opal diffuser that could be complemented with antiglare louver with an angle beam of 105°. Luminaire sets a 10 W LED source with CRI higher than 85 % and a chromatic dispersion lower than 3 SMCD. Fixture has a luminous flux of 201 Lm, with an efficiency of 20,1 Lm/W and a total consumption of 10 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

Item code	11.6105.0003.22
Product type	OUT
Category	Surface
Family	Apliques
Subfamily	Apliques
Materials	Luminaire body built in die-cast aluminium.
Optical system	Luminaire built-in an opal diffuser that could be complemented with antiglare louver.
Installation instructions	Luminaire designed for wall surface mounted.

Pictograms

