




Dimensions

Product dimensions (mm)	ø118 x 800
Packing dimensions (mm)	135 x 135 x 820
Net weight (g)	2700
Gross weight (Kg)	2,95

Scheme

Scheme



Bollard from the TROLL family Polar.
DESCRIPTION

Bollard from the TROLL family Polar setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 4000° K (neutral white) optimised to be used as lighting outdoor areas such as public squares, parks, gardens or outdoor areas of sport buildings. Designed for to be floor fixed. Luminaire body built in extruded aluminium finished in anthracite. Luminaire is IP65 and IK08. Luminaire built-in a high purity aluminium reflector with frontal opal diffuser with an angle beam of floor washer. Luminaire sets a 9 W LED source with CRI higher than 85 % and a chromatic dispersion lower than 3 SMCD. Fixture has a luminous flux of 521 Lm, with an efficiency of 57,9 Lm/W and a total consumption of 9 W. The average life for the luminaire is 35000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

Product

Real power (W)	9
Real luminous flux (Lm)	521
Luminous efficiency (Lm/W)	57,9
Beam angle (°)	100
Life time (h)	35000
IP	65
IK	8
Electrical class insulation	Class 1
Operating temperature	from -20°C to 40°C
Electrical feeding	220..240V, 50/60Hz
Colour	Anthracite
Energy efficiency class	A

Control gear

Control gear included	Yes
Control gear	Electronic Control Gear
Factor de potencia	0,9

Light source

Light source included	Yes
Light source	Led
Nominal power (W)	8
Nominal luminous flux (Lm)	800
Colour temperature (K)	4000
Colour consistency (SDCM)	3
CRI	80

Photometry

Item code	11.7600.0043.22
Product type	OUT
Category	Bollards
Family	Polar
Subfamily	Polar
Materials	Luminaire body built in extruded aluminium.
Optical system	Luminaire built-in a high purity aluminium reflector with frontal opal diffuser.
Installation instructions	Luminaire designed for to be floor fixed.

Pictograms

Photometry

