




Dimensions

Product dimensions (mm) 31,5 x 2000 x 32,5

Scheme

Scheme



Product

IP 20

Electrical class insulation Class 1

Electrical feeding 100..240V, 50/60Hz

Colour White

Control gear

Accessories

2400/33 End cover.

Picture



Scheme



2401D/01/33

DALI Left feeder

Surface DALI PULSE track L: 2000mm

DESCRIPTION

DALI three-phase electrified track of 2 m. Designed for wall or ceiling surface mounted as well as hanging. Body made of extruded aluminium setting copper wires imbibed in PVC profile and finished in white.

Item code 2420D/200/33

Product type IN

Category Tracklights

Family Tracks

Subfamily Trifásico

Pictograms



Picture



Scheme



2401D/02/33

DALI Right feeder

Picture



Scheme




2402D/33

DALI Flexible connector.

Picture



Scheme




2403D/10/33

Continuity connector with DALI connection.

Picture



Scheme



2403D/33

DALI continuity connector.

Picture



Scheme



2407D/01/33

DALI connector "T" Left with possibility of connection.

Picture




2407D/02/33

DALI "T" connector Right with possibility of connection.

Picture



Scheme



2407D/03/33

DALI "T" connector Right with possibility of connection.

Picture



2407D/04/33

DALI connector "T" Left with possibility of connection.

Picture



2408D/01/33

DALI connector "L" Left with possibility of connection.

Picture




2408D/02/33

DALI "L" connector Right with possibility of connection.

Picture



Scheme



2409D/33

DALI "+" connector with possibility of connection.

Picture



Scheme



2413/00

Fastening directly to the ceiling.

Picture



Scheme




2417D/33

DALI adapter with cable.

Picture



Scheme



2431/00

Suspension clamp.

Picture



Scheme



2432/00

Reinforced suspension clamp.

Picture



Scheme



L=182 mm


2434/33

Ceiling rose fastening.

Picture



Scheme



2435/00

M6 threaded stem.

Picture



Scheme



L=2000mm

2438/00

M6 nut.

Picture



Scheme



M6

2439/00

M6 adjustment sleeve.

Picture



Scheme



2440/00

Cable suspension.

Picture



Scheme



L=1500mm

2441/00

Bending tool.

Picture



Scheme

